



Competitive ribbon for demanding applications

Applications

- Automotive interior labels
- Tire labels
- Patient wristbands
- Laboratory labels
- Meat packing labels
- Cosmetics packaging labels
- Rating plates
- Chemical labels
- And many more...



Key benefits

- High print durability
- Broad label substrate compatibility
- Very good printing quality

Recommended substrates

Rough papers	○ ○ ○ ○ ○
Coated papers/tags	● ● ○ ○ ○
Synthetics	● ● ● ● ●

Print quality

0° barcode	● ● ● ● ●
90° barcode	● ● ● ● ●
Small characters	● ● ● ● ●

Print resistance

Abrasion	● ● ● ● ●
Solvent	● ● ○ ○ ○
Heat	180°C 356°F

Printer parameters

Maximum speed: 10 ips (250 mm/s)

Heat settings:



Technical specifications

- Film thickness: 4,5µm
- Total ribbon thickness: <9µm
- Ink melting point: 80°C | 176°F
- Coefficient of friction: Kd < 0,2
- Ink blackness: 2 ODR
- Antistatic designed

Approvals

- REACH / SVHC 1907/2006/EC
- EU Food Contact 1935/2004/EC
- US Food Contact FDA
- RoHS / Heavy Metals 2011/65/EU
- California Proposition 65
- UL 969

Storage conditions

- 12 months recommended
- 20-80% Relative Humidity
- 5-35°C (40-95°F) temperature